

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

1-20. (Cancelled)

21. (Previously Presented) A system for measuring a weight on a vehicle seat comprising:

a seat having a seat bottom;

a seat element for mounting said seat to a vehicle structure;

a seat support member for supporting said seat bottom relative to said seat element;

a bending beam with a first connecting portion for connection to said seat support member, a second connecting portion for connection to said seat element, and a central body portion extending between said first and second connecting portions, said central body portion having a narrowing neck section to concentrate strain in said central body portion; and at least one sensor mounted directly to said narrowing neck section for measuring strain resulting from a weight force applied to said seat bottom wherein said beam includes an extension portion extending beyond one of said first or second connecting portions for supporting an electrical connector for connecting said sensor to a processing unit.

22. (Previously Presented) A system according to claim 21 wherein said bending beam defines a first width at said first and second connecting portions and said neck section defines a second width that is narrower than said first width.

23. (Previously Presented) A system according to claim 22 wherein said first connecting portion provides sole connection of said bending beam to said seat support member and said second connecting portion provides sole connection of said bending beam to said seat element.

24. (Previously Presented) A system according to claim 22 wherein said first and second connecting portions and said central body portion are coplanar.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

25. (Previously Presented) A system according to claim 24 wherein said first and second connecting portions and said central body portion form an hourglass shape.
26. (Cancelled)
27. (Previously Presented) A system according to claim 21 wherein said beam defines a longitudinal axis and said extension portion includes a mount for receiving said electrical connector via a linear insertion force along said longitudinal axis.
28. (Previously Presented) A system according to claim 27 wherein said electrical connector includes a first connector portion directly attached to one end of said beam and a second connector portion selectively mateable to said first connector portion to complete electrical connection between said sensor and said processing unit.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

29. (Previously Presented) A system for measuring a weight on a vehicle seat comprising:
- a seat having a seat bottom;
  - a seat element for mounting said seat to a vehicle structure;
  - a seat support member for supporting said seat bottom relative to said seat element;
  - a bending beam with a first connecting portion for connection to said seat support member, a second connecting portion for connection to said seat element, and a central body portion extending between said first and second connecting portions, said central body portion having a narrowing neck section to concentrate strain in said central body portion;
  - at least one sensor mounted directly to said narrowing neck section for measuring strain resulting from a weight force applied to said seat bottom; and
  - traces for electrically connecting said sensor to an electronics package wherein said sensor and said traces are screen printed on said beam.
30. (Previously Presented) A system according to claim 21 wherein said first connecting portion includes a first aperture for receiving a first fastener and said second connecting portion includes a second aperture for receiving a second fastener.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

31. (Previously Presented) A system for measuring a weight on a vehicle seat comprising:
- a seat having a seat bottom;
  - a seat element for mounting said seat to a vehicle structure;
  - a seat support member for supporting said seat bottom relative to said seat element;
  - a bending beam with a first connecting portion for connection to said seat support member, a second connecting portion for connection to said seat element, and a central body portion extending between said first and second connecting portions, said central body portion having a narrowing neck section to concentrate strain in said central body portion wherein said first connecting portion includes a first aperture for receiving a first fastener and said second connecting portion includes a second aperture for receiving a second fastener;
  - at least one sensor mounted directly to said narrowing neck section for measuring strain resulting from a weight force applied to said seat bottom; and
  - a first insert mounted within said first aperture and having a first internal central bore for receiving said first fastener and a first stepped portion formed about an external perimeter of said first insert wherein said first stepped portion has a greater diameter than said first aperture such that a first gap is formed between said seat support member and said beam and including a second insert mounted within said second aperture and having a second internal central bore for receiving said second fastener and a second stepped portion formed about an external perimeter of said second insert wherein said second stepped portion has a greater diameter than said second aperture such that a second gap is formed between said seat element and said beam.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

32. (Previously Presented) A system for measuring a weight on a vehicle seat comprising:

- a seat having a seat bottom;
- a seat element for mounting said seat to a vehicle structure;
- a seat support member for supporting said seat bottom relative to said seat element;
- a bending beam with a first connecting portion for connection to said seat support member, a second connecting portion for connection to said seat element, and a central body portion extending between said first and second connecting portions, said central body portion having a narrowing neck section to concentrate strain in said central body portion wherein said first connecting portion includes a first aperture for receiving a first fastener and said second connecting portion includes a second aperture for receiving a second fastener;
- a first shim having a first internal central bore for receiving said first fastener and a first connector for attaching said first shim to said beam and including a second shim having a second internal bore for receiving said second fastener and a second connector for attaching said second shim to said beam; and
- at least one sensor mounted directly to said narrowing neck section for measuring strain resulting from a weight force applied to said seat bottom.

33. (Previously Presented) A system according to claim 32 wherein said first shim is mounted in direct engagement with an upper surface of said first connecting portion and said second shim is mounted in direct engagement with a lower surface of said second connecting portion.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

34. (Previously Presented) A system according to claim 32 wherein said first connector comprises a first transversely extending tab and said first connecting portion includes a first slot spaced outwardly from said first aperture for receiving said first transversely extending tab and wherein said second connector comprises a second transversely extending tab and said second connecting portion includes a second slot spaced outwardly from said second aperture for receiving said second transversely extending tab.

35. (Previously Presented) A system according to claim 32 wherein said first connector comprises at least one first hole and said first connecting portion includes at least one first corresponding hole spaced outwardly from said first aperture and aligned with said first hole for receiving a first pin and wherein said second connector comprises at least one second hole and said second connecting portion includes at least one second corresponding hole spaced outwardly from said second aperture and aligned with said second hole for receiving a second pin.

36. (CANCELLED)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041U501
DATE OF RESPONSE	ART UNIT		EXAMINER
7th October 2004	2636		Julie Bichngoc LIEU

37. (Currently Amended) [~~An assembly according to claim 36~~] A weight sensor assembly for measuring a weight on a vehicle seat comprising:

a bending beam having a first connection portion engageable with an upper seat structure and a second connection portion engageable with a lower seat structure;

a bendable central body portion coplanar with and extending between said first and second connection portions, said central body portion having a narrowing neck to concentrate strain in said central body portion; and

a strain gage assembly mounted directly to said narrowing neck for measuring the strain at said central body portion resulting from a weight force being exerted against the upper seat structure wherein said beam includes an extension portion extending beyond one of said first or second connection portions for supporting an electrical connector to connect said strain gage to a processing unit.

38. (Previously Presented) An assembly according to claim 37 wherein said beam defines a longitudinal axis and said extension portion includes a mount for receiving said electrical connector via a linear insertion force along said longitudinal axis.

39. (Previously Presented) An assembly according to claim 38 wherein said electrical connector includes a first connector portion directly attached to one end of said beam and a second connector portion selectively mateable to said first connector portion to complete electrical connection between said sensor and said processing unit.

40. (Previously Presented) An assembly according to claim 37 including an electronics package mounted on said beam adjacent to said electrical connector.

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041 US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

41. (Previously Presented) An assembly according to claim 40 including traces for electrically connecting said strain gage assembly to said electronics package wherein said strain gage assembly, said traces, and said electronic package are screen printed on said beam.

42. (Previously Presented) An assembly according to claim 41 including a protective member for enclosing said electronics package.

43. (Currently Amended) [~~An assembly according to claim 36~~] A weight sensor assembly for measuring a weight on a vehicle seat comprising:

a bending beam having a first connection portion engageable with an upper seat structure and a second connection portion engageable with a lower seat structure;

a bendable central body portion coplanar with and extending between said first and second connection portions, said central body portion having a narrowing neck to concentrate strain in said central body portion; and

a strain gage assembly mounted directly to said narrowing neck for measuring the strain at said central body portion resulting from a weight force being exerted against the upper seat structure wherein said first connecting portion includes a first aperture for receiving a first fastener and said second connecting portion includes a second aperture for receiving a second fastener, said first fastener providing sole connection of said beam to said upper seat structure and said second fastener providing sole connection of said beam to said lower seat structure.



APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.
10/010,471	8th November 2001	Brian CURTIS	2000P09041US01
DATE OF RESPONSE	ART UNIT	EXAMINER	
7th October 2004	2636	Julie Bichngoc LIEU	

44. (Previously Presented) An assembly according to claim 43 including a first insert mounted within said first aperture and having a first internal central bore for receiving said first fastener and a first stepped portion formed about an external perimeter of said first insert wherein said first stepped portion has a greater diameter than said first aperture such that a first gap is formed between said upper seat structure and said beam and including a second insert mounted within said second aperture and having a second internal central bore for receiving said second fastener and a second stepped portion formed about an external perimeter of said second insert wherein said second stepped portion has a greater diameter than said second aperture such that a second gap is formed between said lower seat structure and said beam.

45. (Previously Presented) An assembly according to claim 44 including a first shim having a first center opening in alignment with said first internal central bore for receiving said first fastener and a second shim having a second center opening in alignment with said second internal bore for receiving said second fastener wherein said first shim is positioned between an upper surface of said first connecting portion and said upper seat structure and said second shim is positioned between a lower surface of said second connecting portion and said lower seat structure.

46. - 59. (CANCELLED)